## NEPTCO DATA

3 in 1 PREMISE MULETAPE

- Eliminates the Potential for Duct Cutting
- Lower Elongation Reduces **Snap-back and Enhances Worker Safety**
- Reduces Tension at the Start of a Pull
- Sequential Footage or **Metric Markings**
- Reduces Material, Inventory and Freight Costs
- Pulling Strength 200 lbs. to 6000 lbs.
- Patent Pending



## 3 IN 1 PREMISE MULETAPE® PRODUCT ORDERING INFORMATION

ITEM #	PRODUCT	STRENGTH lbs. (kg)	TYPICAL BOWLINE STRENGTH lbs. (kg)	TYPICAL MULEKNOT STRENGTH lbs. (kg)	PAIL QUANTITY ft. (km)	APPROX. PAIL WEIGHT lbs. (kg)	PAILS PER PALLET
41271	WP400P	400 (182)	190 (86)	300 (136)	4,500 (1.4)	13 (6)	27
41325	WP1800P	1800 (818)	830 (377)	1400 (636)	1,300 (.4)	14 (6.4)	27



NEPTCO only warrants that its products will work in a manner consistent with the capabilities described. This information corresponds to our current knowledge of the subject and it is not intended to substitute for any testing you may need to conduct to determine suitability of our product for your particular purpose.

Except for the express warranty and limited remedies described herein, NEPTCO DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

The Buyer's remedies under the limited warranty stated above shall be limited to a return of the purchase price of the product. NEPTCO and its authorized agents shall not be liable for any other damages including consequential damages, incurred in connection with the use or performance of the product.

This warranty shall be void if the product has been tampered with or improperly used.

NEPTCO reserves the right to improve, enhance, and / or modify the features and specifications of these products.



Pulling tapes, such as FLATLINE® and MULETAPE®, are intended for use only by cable installation professionals. Do not strap, bind or lift items with this product.

