

# QUADTAPE®

## Detectable MULETAPE®

### Description

Flat, woven, polyester tape with four insulated metallic conductors offer a reliable means of detecting all-dielectric cables and empty conduit.

### Features & Benefits

- ▲ Lubricated for easy installation and reduced friction
- ▲ Durably printed with sequential footage or meter markings
- ▲ Low elongation for enhanced worker safety
- ▲ Four 22 gauge corrosion-resistant conductors provide enhanced conductivity at a wide range of frequencies (4.4 ohms/mft.), and are compatible with any standard transmitting/receiving equipment.
- ▲ Packaged on sturdy wooden or plastic reels
- ▲ NEPTCO Detectable MULETAPE identification tags included with every reel
- ▲ Easily spliced using conventional methods or the MULEKNOT™



*Please refer to NEPTCO's applications bulletin on grounding and splicing Detectable MULETAPE.*

*Please refer to NEPTCO's applications bulletin for instructions on splicing using a MULEKNOT.*

### QUADTAPE DETECTABLE MULETAPE PRODUCT ORDERING INFORMATION

PRODUCT	STRENGTH		MINIMUM REEL LENGTHS		APPROX. WIDTH
	lbs	(kg)	ft	(km)	
DT1250/4P	1250	(568)	3000	(1)	9/16"

PLEASE SEE REVERSE SIDE FOR ADDITIONAL INFORMATION



NEPTCO • 30 Hamlet Street, Pawtucket, Rhode Island 02861  
Phone: 401.722.5500 • Toll-free: 800.354.5445 • Fax: 401.722.6378 • Web: [www.muletape.com](http://www.muletape.com)

# QUADTAPE®

## Detectable MULETAPE®

### Conductor Data

AWG	22 Tin Coated Copper
Diameter	.0253" Nominal
Maximum Voltage	300 V
Resistivity	4.4 OHMS per MFT
Tensile Strength	50,000 psi Nominal
Break Strength	25 lbs. Nominal
Elongation	20%

### Insulation Data

Type	Extrusion Friendly Copolymer - Orange Color
Thickness	.008" Nominal
Dielectric Constant	2.24 @ 1 MHZ
Dry Dielectric	850V/MIL
Wet Dielectric	800V/MIL



## WARNING

**Detectable MULETAPE®: To promote detection of underground cables and utilities – As with any conductor, it has the potential to transfer electrical energy. Do not pull, strap, bind or lift items with this product.**

NEPTCO warrants that its products will work in a manner consistent with the capabilities described in the data sheet. This warranty shall be void if the product has been tampered with or improperly used. Except for the express warranty and limited remedies described above, NEPTCO disclaims all other warranties including implied warranties. NEPTCO and its authorized agents shall have no other liability beyond the price of the product for damages to a purchaser, including consequential damages, occurring in connection with the use or performance of the product.



NEPTCO • 30 Hamlet Street, Pawtucket, Rhode Island 02861  
 Phone: 401.722.5500 • Toll-free: 800.354.5445 • Fax: 401.722.6378 • Web: [www.muletape.com](http://www.muletape.com)  
 © 2005 NEPTCO • Printed in U.S.A. • 07/10  
 MULETAPE and QUADTAPE are registered trademarks of NEPTCO, Incorporated

