

## Description:

Flat, woven, low shrink (extrudable grade) polyester tape used for installing fiber optic, copper, and coaxial cables in underground conduit.

Product: Low shrink MULETAPE WP - standard MULETAPE

% shrinkage: 3% to 5% 10% to 12%

Note: % shrinkage is affected by extrusion temperature and line speed



## NEPTCO Low Shrink Polyester MULETAPE Product Offering

Low Shrink Product	Strength lbs	(kg)	Typical Reel Lengths mft	Lubricated	Approximate Width	Weight per mft (lbs/mft)
LP400P	400	(189)	100	Y	1/4"	2.459
LP600P	600	(273)	100	Y	3/8"	3.53
LP900P	900	(409)	100	Y	7/16"	4.85
LP1000P	1000	(455)	100	Y	15/32"	5.74
LP1250P	1250	(568)	100	Y	1/2"	6.71
LP1800P	1800	(818)	65	Y	5/8"	9.66
LP2500P	2500	(1136)	40	Y	3/4"	13.23



Pulling tapes, such as FLATLINE® and MULETAPE®, are intended for use only by cable installation professionals. Do not strap, bind or lift items with this product.

NEPTCO only warrants that its products will work in a manner consistent with the capabilities described. This information corresponds to our current knowledge of the subject and it is not intended to substitute for any testing you may need to conduct to determine suitability of our product for your particular purpose. Except for the express warranty and limited remedies described herein, NEPTCO DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. The Buyer's remedies under the limited warranty stated above shall be limited to a return of the purchase price of the product. NEPTCO and its authorized agents shall not be liable for any other damages including consequential damages, incurred in connection with the use or performance of the product. This warranty shall be void if the product has been tampered with or improperly used. NEPTCO reserves the right to improve, enhance, and / or modify the features and specifications of these products.