

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Roofing Systems

[See General Information for Roofing Systems](#)

C I M INDUSTRIES INC
23 ELM ST
PETERBOROUGH, NH 03458-1011 USA

R9476

FLUID APPLIED COATING SYSTEMS

Class A

1. Deck: C-15/32

Deck joints covered with 3 in. self-adhering aluminum foil tape (UL Listed).

Incline: 2

Coating: — 2 coats "C.I.M. 1000 Membrane" consisting of "C.I.M. 1000 Premix" and "C.I.M. 1000 Activator" mixed 9:1 by volume, at 1-1/2 gal/sq coat.

Surfacing: — Gravel, at 400 lbs/sq, embedded in wet top coat.

2. Deck: NC

Primer (Optional): — C.I.M. 20 at 1/4 gal/sq.

Membrane: — C.I.M. 800 at 3 3/4 gal/sq.

Top Coat: — C.I.M. 810 at 3 gal/sq.

Incline: 1/4

[Last Updated](#) on 2006-01-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."