



CIM ECO 1061 PREMIX

Mix With CIM ECO ACTIVATOR

Keep Out of Reach of Children



WATER QUALITY

DRINKING WATER
SYSTEM COMPONENT

NSF/ANSI CAN 61 66YS

Meets Health Effects Requirements
of NSF/ANSI CAN 600

UL File No. M-17445

0 g/L V.O.C.



Made in the U.S.A.

Keep Dry
Mix Thoroughly Before Using
Do Not Thin
Contents: 3.85 g / 14.6 L



Children can fall into
bucket and drown.

Keep children away from
bucket with even a small
amount of liquid.

Los niños corren peligro
de caerse dentro del balde
y ahogarse.

Mantener a los niños
lejos de los baldes,
incluso cuando sólo
tengan una pequeña
cantidad de líquido.

CIM ECO 1061 Premix

Hazard statement

None

Precautionary statement

Prevention

Do not eat, drink or smoke when using this product.

Response

Take off contaminated clothing and wash it before reuse.

Storage

Store away from incompatible materials.

Supplemental information

All components are on the U.S. EPA TSCA Inventory list.

C.I.M. Industries Inc.
6900 NELMS STREET
HOUSTON, TX 77061
800-543-3458

Emergency Contact
Chemtree - 24 hours
US: 800-424-9300
Int: 703-527-3887

APPLICATION - This product is for professional use only. The user determines suitability for intended use and assumes all risk and liability for application. All purchases and uses subject to the warranty below.

PRECAUTIONS - Avoid contamination with water. Keep container tightly closed. All mixing equipment and surfaces where material is applied must be absolutely dry. All material should be applied within 30 minutes after mixing. Warmer temperatures reduce the working time. Apply when ambient and material temperatures are 60°F or above. Consult C.I.M.'s Cold Weather Instruction Guide (IS-11) for temperatures below 60°F. Do not apply in wet weather or when rain is imminent.

DESCRIPTION & RECOMMENDED USE - CIM ECO 1061 is a viscous liquid component used in two-component blends of CIM ECO 1061 Premix and CIM ECO Activator to form an impermeable seamless monolithic membrane on vertical surfaces. The material cures chemically at ambient temperature to form a tack free peelable membrane within approximately four hours.

COVERAGE - Coverage varies with surface texture and type of application. Refer to current C.I.M. Industries Inc. published documents for coverage rates.

DIRECTIONS - Read and understand the published CIM ECO 1061 Technical Data Sheet for this product before opening this container. Use one .75 gallon (2.8 liter) container of CIM ECO Activator per 3.85 gallon (14.6 liter) part of CIM ECO 1061 Premix. CIM ECO 1061 must be mixed in proper ratios. Do not mix partial units. A critical component in application success is proper mixing and application technique. Thoroughly blend with CIM ECO Activator by mechanical means and apply in strict accordance with printed instructions and specifications provided by C.I.M. Industries Inc.

DISPOSAL INFORMATION - When material is fully reacted with CIM ECO Activator, it can be disposed of at a landfill. Check your local requirements. When discarding material not fully reacted, this material is hazardous waste. Disposal should be in accordance with applicable local, state and federal regulations.

WARRANTY

CIM warrants its Membrane (1) that for a period of five (5) years from the date of shipment to the initial purchaser the Membrane Products, when mixed in accordance with the prescribed length of time, do not become brittle or crack and (2) will provide a water barrier and (3) that the Membrane Products will, at the time of manufacture, conform to CIM's current quality standards. Notice in writing of water leakage or other potential claim or breach under this warranty, must be provided to CIM within seven (7) days of the claimed leakage, claim or breach.

If CIM determines, at its sole discretion, that a breach of warranty has occurred, CIM's sole responsibility shall be repayment of the purchase price of the non-conforming Membrane Product or, at CIM's option, resupply of conforming Membrane Product to replace the non-conforming Membrane Product. No warranty shall apply to any Membrane Product subjected to misuse, improper installation, repair or alteration, neglect, accident, abnormal conditions of operation or use in any manner contrary to instructions.

EXCEPT FOR THE EXPRESS WARRANTIES CONTAINED IN THIS WARRANTY CIM MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES, CONCERNING ITS MEMBRANE PRODUCTS.

IN NO EVENT SHALL CIM BE LIABLE OR OBLIGATED IN ANY MANNER FOR ANY SPECIAL, INCIDENTAL, EXEMPLARY OR CONSEQUENTIAL DAMAGES OF ANY KIND, INCLUDING BUT NOT LIMITED TO, LOSS OF PROFITS, REGARDLESS OF THE FORM OF ACTION, WHETHER BY CONTRACT, TORT, NEGLIGENCE, STRICT PRODUCT LIABILITY, OR OTHERWISE.

C.I.M. Industries Inc.
www.cimindustries.com

75912